

Technical Datasheet

EN ISO 13485 certified		
Article - No:	11-432-6000	Revision: 6
Remarks	max. volume: 80ml / working volume: 60 ml	single use only

Specification

Product	Screw cap container PP, 60ml, Ø50X60mm, cap pre-assembled , container transparent, cap green grading 3 sided, every 10ml, sterile EO, CE/IVD
Classification	CE/IVD
Colour	container transparent, cap green
Graduation	grading 3 sided, every 10ml
Nominal Capacity	60ml
Material Characteristics	container: polypropylene (PP) cap: high-density polyethylene (HDPE)
Temperature range	-40°C - 120°C
Product Characteristics	leak proof of not less than 95 KPa (0,95 bar, 14 psi) biologically inert physiologically harmless no heavy metals according to EC/94/62
Purity Grade	do not contain any pyrogens
Sterilisation Process	gas sterilisation by ethyleneoxid
Shelf - Life	36 months at controlled storage conditions
Packaging	pcs per bag: 250 pcs per carton: 250 pcs per pallet: 8.000
Storage	dry condition: 40%-60% rel. humidity bags / cases orig. closed storage temp. +2°C to max. +30°C pal. not stackable

Approved by nerbe plus quality department

00-000-0001/06.2020

