

Technical Datasheet

EN ISO 13485 certified		
Article - No:	11-492-0000	Revision: 7
Remarks	max. volume: 1000 ml / working volume: 800 ml	single use only

Specification

Product	Screw cap container PP, 800 ml, Ø121,5X140,5mm, cap seperatly packed, container transparent, cap green, grading 3 sided, every 10ml, sterile, CE/IVD
Classification	CE/IVD
Colour	container transparent, cap green
Graduation	grading 3 sided, every 10ml
Nominal Capacity	800 ml
Material Characteristics	container: polypropylene (PP) cap: high-density polyethylene (HDPE)
Temperature range	-40°C - 120°C
Product Characteristics	leak proof of not less than 50 KPa (0,5 bar, 7,25 psi) biologically inert physiologically harmless no heavy metals according to EC/94/62
Purity Grade	manufactured in clean rooms of ISO Class 8 or better (DIN EN ISO 14644-1)
Shelf - Life	60 months at controlled storage conditions
Packaging	pcs per bag: 44 pcs per carton: 44 pcs per pallet: 1.408
Storage	dry condition: 40%-60% rel. humidity bags / cases orig. closed storage temp. +2°C to max. +30°C pal. not stackable
Approved by nerbe plus quality department	

00-000-0001/06.2020

