

Technical Datasheet

EN ISO 13485 certified	
Article - No:	02-552-6000
Revision:	3
Remarks	single use only

Specification

Product	Test tube PP with fitted screw cap PE, 30ml, Ø25x107 mm, conical bottom, skirted, tube transparent, cap natural, grad., sterile R, max. RCF 5.000g, autocl. up to 121°C
Dimensions	outer diameter: 25,00 mm (+/- 0,2 mm) height: 107,00 mm (+/- 0,2 mm)
Colour	tube transparent, cap natural
Graduation	grad.
Nominal Capacity	30ml
Material Characteristics	tube: polypropylene (PP) cap: polyethylene (PE)
Temperature range	tube: -196°C up to +121°C cap: -50°C up to +80°C
Autoclavability	autocl. up to 121°C
Centrifugation	max. RCF 5.000g
Product Characteristics	biologically inert physiologically harmless no heavy metals according to EC/94/62
Purity Grade	do not contain any pyrogens
Sterilisation Process	radiation sterilization SAL 10-6
Shelf - Life	36 months at controlled storage conditions
Packaging	pcs per bag: 100 pcs per carton: 500 pcs per pallet: 12.000
Storage	dry condition: 40%-60% rel. humidity bags / cases orig. closed storage temp. +10°C to max. +30°C pal. not stackable

Approved by nerbe plus quality department

00-000-0001/06.2020

